

NOTES:

- . STREET WIDTH USE DEFINED IN SUBDIVISION REGULATION MATRIX
- 2. PAVEMENT THICKNESS DEPENDENT UPON PAVEMENT ANALYSIS & TO BE APPROVED BY CITY ENGINEER
- 3. ALL SUBGRADE & FILL BELOW PAVEMENT SHALL BE TESTED AND MEET GRAND ISLAND CITY STANDARD SPECIFICATIONS FOR DENSITY AND MOISTURE
- 4. I2'-0" TRANSVERSE JOINTS
- 5. CENTERLINE GRADE MINIMUM 0.3%
- 6. EXPANSION JOINTS LOCATED AT END OF INTERSECTION RETURNS MAXIMUM DISTANCE 500 FEET
- 7. STRIPING TO BE APPROVED BY PUBLIC WORKS DEPARTMENT
- 8. NO PARKING
- 9. INFORMATION PROVIDED HEREIN REQUIRES USE OF ADDITIONAL CITY STANDARD PLAN DETAILS FOR PROPER CONSTRUCTION



41' COMMERCIAL STREET STANDARD PAVEMENT CROSS SECTION	PLAN		20)4	
	SHEET		I 0	F	I
CITY STANDARD PLANS & SPECIFICATIONS GRAND ISLAND NERBASKA	DRAWN BY:	TJY	DATE:	DEC 2	013
	REVISED BY:	MLS	DATE:	JAN 2	021
	APPROVED BY:	KJK	DATF:	MAR 2	'021