



NOTES:

1. STREET WIDTH USE DEFINED IN SUBDIVISION REGULATION MATRIX
2. ALL SUBGRADE & FILL BELOW PAVEMENT SHALL BE TESTED AND MEET GRAND ISLAND CITY STANDARD SPECIFICATIONS FOR DENSITY AND MOISTURE
3. 12'-0" TRANSVERSE JOINTS
4. CENTERLINE GRADE MINIMUM 0.3%
5. EXPANSION JOINTS LOCATED AT END OF INTERSECTION RETURNS MAXIMUM DISTANCE 500 FEET
6. NO CURB, NO GUTTER, NO SIDEWALK, NO PARKING
7. INFORMATION PROVIDED HEREIN REQUIRES USE OF ADDITIONAL CITY STANDARD PLAN DETAILS FOR PROPER CONSTRUCTION

| | | | |
|--|--|-------|--|
| | 30' INDUSTRIAL STREET STANDARD PAVEMENT CROSS SECTION | PLAN | 207 |
| | | SHEET | I OF I |
| | CITY STANDARD PLANS & SPECIFICATIONS GRAND ISLAND, NEBRASKA | | DRAWN BY: T J Y DATE: DEC 2013 REVISED BY: M L S DATE: JAN 2021 APPROVED BY: K J K DATE: MAR 2021 |