



NOTES:

1. 15' MINIMUM RADIUS ON STANDARD COMMERCIAL OPENINGS & 50' MINIMUM RADIUS ON COMMERCIAL WITH TRUCK TRAFFIC DELIVERIES
2. WIDER OPENINGS AND/OR SMALLER RADII MAY BE USED ONLY WHEN APPROVED BY CITY ENGINEER PRIOR TO CONSTRUCTION
3. IF THERE IS LESS THAN 15' BETWEEN BACK OF CURB & PROPERTY LINE, APPROACH SHALL EXTEND ONTO PRIVATE PROPERTY
4. PORTLAND CEMENT CONCRETE TO BE 47B MODIFIED WITH MINIMUM 6" OF THICKNESS
5. CURBS CAN BE TAPERED FROM FULL CURB TO NO CURB IN THE RADIUS LENGTH OR BE MAINTAINED AS FULL CURB WHICHEVER FITS THE PRIVATE PROPERTY DESIGN

	STANDARD COMMERCIAL DRIVEWAY	PLAN	219
		SHEET	1 OF 1
	CITY STANDARD PLANS & SPECIFICATIONS GRAND ISLAND, NEBRASKA		DRAWN BY: LDC DATE: FEB 1989 REVISED BY: MLS DATE: MAY 2021 APPROVED BY: KJK DATE: MAY 2021